



Engineering Solutions

Liquid Tight Multi-Hole Cordgrips
Perfect for dependable seals and safe routing



Liquid Tight Multi-Hole Cordgrips NPT and PG Hubs



Features:

- All accompanying Cordgrips are made of nylon construction with TPE sealing glands that resist salt water, weak acids, gasoline, alcohol, oil, grease and common solvents. This feature is not assessed by UL certification or testing.
- Temperature Rating: -22F (-30°C) to 212°F (100°C).
- IP Rating: IP 68 per DIN 40050 up to 70 psi (5 bar) water pressure.
- Flammability Rating: 94V-2 Standard.
- Locknuts are NOT included for NPT. Locknuts are included for PG.
- A solution for protecting multiple wires through a single cordgrip. Use fewer cordgrips to save money!
- Standard color black. Consult factory for Cordgrips molded in other colors.

Specifications:

Material:	6/6 Nylon (body) with TPE (gland)
Flammability Rating:	94V-2 Standard
Temperature Rating:	-22°F (-30°C) to 212°F (100°C)
IP Rating:	IP 68 per DIN 40050 up to 70 psi (5 bar) water pressure

For more information, contact EFC International:

St. Louis (Corporate)	800-888-3326	(fax: 314-434-2902)
Chicago	800-727-8466	(fax: 630-539-7070)
Atlanta	800-541-9019	(fax: 770-663-8484)

Explore other EFC Engineering Solutions on-line at: www.efc-intl.com