



Engineering Solutions


RIV-FLOAT®

Perfect for off center applications!

Ensure easy, attachment of center applications. designed for post applications where nuts, floating nut are used.



RIV-FLOAT™ Installed



Cross Section of RIV-FLOAT™ Installed

accurate, and fast components in off **RIV-FLOAT®** was finish installation in cage nuts, clinch plates or weld nuts

The internally floating threads on **RIV-FLOAT®** allow for component attachments in off center applications and can accommodate for tolerance stack up in the manufacturing process. The floating nut aligns to drive the angle of the screw thus eliminates cross threading and spin out.

Technical Data

- .020" Radial float
- Large (RFL) and small flange (RFK) series available in 8-32, 10-32, ¼-20, M4, M5 and M6
- Mechanically locked RIV-FLOAT® is available with prevailing torque feature to IFI Spec 100/107
- Zinc electroplated to 8 μ m with trivalent chromate – 120/240

RIV-FLOAT® Rivet nut hand tool installation kits offered by EFC:

EFC Part #	Description	Qty in Kit
06X0300424-KIT	Metric Kit M4, M5 and M6	80 (20 ea)
06X0300425-KIT	6-32/8-32 Mini Inch Kit	40 (20 ea)
06X0300426-KIT	¼-20 and 10-32	30 (10,20)
06X0300427-KIT	6-32 .027-.130	15
06X0300428-KIT	8-32 UNC .027-.130	15
06X0300429-KIT	10-32 UNF .027-.150	15
06X0300430-KIT	¼-20 UNC .027-.150	10
06X0300431-KIT	M4 x .7 ISO .7-3.3	15
06X0300432-KIT	M5 x .8 ISO .7-3.8	15
06X0300433-KIT	M6 x 1 ISO .7-3.8	11



Installed with MS 50 Hydro-pneumatic tool with RIV-FLOAT® nose piece.

Atlanta | St. Louis | Chicago | Toronto

800.888.3326

www.efc-intl.com